

Signalyst HQPlayer 4 Embedded

[Help](#)

Generic

Title

HQPlayer

Backend

Network Audio

Output mode

PCM

Fixed volume (dBFS)

☐ enabled

Startup volume (dBFS)

-12

Channels

2

Options

☒ Auto rate family

Log file

☐ enabled

/tmp/hqplayerd.log

DSD sources

☐ Direct SDM

Integrator

IIR

SDM-SDM Conversion

wide

☐ Gain +6 dB

SDM-PCM Conversion

poly-short-lin

Noise filter

standard

PCM settings

1x Filter

closed-form-M

Nx Filter

closed-form-M

Dither

NS5

Sample rate

Auto

Rate limit

1536000

SDM settings

1x Oversampling

minringFIR-mp

Nx Oversampling

minringFIR-mp

Modulator

ASDM5EC

Bit rate

Auto

Rate limit

11289600

ALSA backend

Device

Current (SA9023 USB Audio: USB Audio)

Channel offset

0

DAC bits

0 (0 = default)

Buffer time

100 ms (0 = default)

- ☐ DoP
- ☒ 48k DSD

Network Audio backend

Device

Current (alnaa: USB HiRes Audio: USB Audio)

DAC bits

0 (0 = default)

Buffer time

100 ms (0 = default)

- ☐ DoP
- ☒ 48k DSD
- ☒ IPv6

Apply

[Main](#) [Input](#) [Library](#) [Configuration](#) [Speakers](#) [Convolution](#) [Matrix](#) [Backup](#)
[Restore](#) [About](#) [Authentication](#) [Key](#) [Log](#)

Copyright (C) 1998-2019 Jussi Laako / Signalyst. All rights reserved.