

Sonus faber
IL CREMONESE
ex3me

SONUS FABER LAUNCHES THE NEW EXCLUSIVE LIMITED-EDITION II CREMONESE EX3ME
INSPIRED BY THE 30TH ANNIVERSARY PROJECT EX3MA

INTRODUCING THE II CREMONESE EX3ME

(September 22nd, 2020) – Sonus faber is proud to introduce the new special edition II Cremonese ex3me. Introduced in 2015 with the intention of completing the Sonus faber Homage Collection, the speaker was named after a traditional Italian violin, the II Cremonese. This violin is the most famous among the master Antonio Stradivari's creations. Due to its superb sound capability, the new II Cremonese speaker immediately placed among the ranks of Sonus faber's Reference Collection catalogue, becoming a favorite among the Sonus faber R&D team members.

This predilection turned the II Cremonese into a crucial internal Sonus faber work instrument, serving as an effective test bench for the development of various technical solutions due to the innate versatility of its electroacoustic configuration.

This concept led to the idea of using II Cremonese as the foundation for a unique loudspeaker system characterized by new technical features with a precise performance target: absolute neutrality working around the behavior of both the top and bottom ends of the audio spectrum.

II Cremonese ex3me embodies a loudspeaker system coming to life by combining elements from the original project, such as midrange and woofers, with iconic solutions derived from Sonus faber's 30th Anniversary Celebration concept speaker model, Ex3ma.

Several new design solutions contribute to a precious electro-acoustic jewel available in a special, limited run of 50 pairs embellished by the return of a traditional Sonus faber finish, the classic "Red Violin".

THE ELECTROACOUSTIC PROJECT

- **High frequencies**

From Ex3ma, II Cremonese ex3me inherits its most iconic component, the Beryllium DLC tweeter.

Exclusively for these 50 pairs, Sonus faber approaches this transducer construction with a material well known in the high-fidelity industry since the 70's. Thanks to its formidable physical characteristics, Beryllium has unique and beneficial characteristics in terms of transparency and micro dynamics. The typical sound presentation of its "metallic flavor", due to the material's resonant frequency above 20 kHz, is mitigated by the treatment of 'D.L.C. (Diamond Like Carbon),' which essentially changes the mechanical nature of the beryllium while leaving its mass relatively unaltered.



Sonus faber
IL CREMONESE
ex3me

With a treatment called "Chemical Vapor Deposition" a layer of D.L.C. is deposited on the diaphragm surface, turning it black and giving the Beryllium the amorphous nature and the strength of the diamond. As a result, the new diaphragm is increasingly rigid with a nearly unperceivable resonant frequency (above 35 kHz), making it capable of extremely fast sound, very detailed and airy and free of coloration.

The powerful Neodymium magnetic system and the rear decompression chamber made of Eral (Aluminum alloy) CNC machined from solid billets, guarantee extreme dynamic linearity and maximum resolution in reproduction.

- **Middle frequencies**

The mid-frequency dedicated transducer remains similar to the original model in order to preserve the iconic "Voice of Sonus faber". This 180mm midrange features a cone manufactured according to the classic Sonus faber recipe: an air-dried, non-pressed blend of cellulose pulp, Kapok, Kenaf, and other natural. This treatment guarantees a natural sound with increased transparency and greater detail.

The Neodymium magnetic motor system is completely "Eddy Current Free" thanks to a copper Faraday ring strategically placed in the gap. The final touch a 1.5" voice coil made in Copper Clad Aluminum Winding (CCAW).

- **Low frequencies**

The two 180mm woofers of Il Cremonese ex3me are implemented in an independent acoustic chamber, acoustically amorphous and fitted with down firing 'Stealth Reflex' ducts. Their cones feature the 'sandwich' membrane made of two sheets of our cellulose pulp recipe with a layer of hi-tech rigid syntactic foam in between them. This construction technique provides maximum coherence with the mid-high units and ensures, speed, rigidity and low mass in the driver. These woofers cones are mounted on the Sonus faber die-cast Aluminum baskets designed for structural rigidity and maximum ventilation to the moving parts.

- **Ultra-low frequencies**

The 2 side-firing infrawoofers featured in each loudspeaker are designed ad hoc for this project. Their diaphragm is made from nanocarbon fiber, used not only for its incredible structural rigidity, but also as a call back to the mid-woofer of Ex3ma-- the project that gave the name and inspiration for Il Cremonese ex3me. This Tri-laminated sandwich cone diaphragm features Nomex honeycomb core and manages the driver's excursion and resistance to flexing, even at extreme amplitudes.

Like the woofer, the infra-woofers are implemented in independent acoustic chambers, acoustically amorphous and each fitted with their own 'Stealth Reflex' duct.

- **The Crossover network**

The blend between the Beryllium DLC tweeter and the midrange is obtained courtesy of a totally redesigned mid-high crossover network, using non-inductive resistors and air core inductors. Capacitors are Mundorf Evo Silver Oil and Evo Gold Oil designs, known for their supreme performance in audio



Sonus faber
IL CREMONESE
ex3me

circuitry. The entire crossover network implements Paracross Topology™, a special circuit making the crossover less sensitive to radio-frequency interference, lowering noise floor.

The Design

The overall aesthetic design of Il Cremonese ex3me does not stray from the original model, except for the detail of the tweeter- which diverges from the iconic "arch" of the D.A.D. system in favor of the protection grille applied in front of the Beryllium D.L.C. dome.

The design maintains the "Romboidal Diamond Design." The 5-sided cabinet breaks the classic rules of Lute or Lyre shape. Taking inspiration from the shape of Sonus faber's Liliun Collection, Il Cremonese has cleaner lines with a more edgy design aesthetic. Maintaining the absence of parallel walls ensures that the acoustic characteristics are not compromised by standing waves or internal reflections.

This solid cabinet is further strengthened by two "Dampshelves" machined from solid billet aluminum forming the top and bottom of the cabinet. These structural elements increase rigidity and lower resonance that contributes to the attenuation of spurious noise that contaminates the purity of the musical message.

Spurious micro-vibration is grounded to the Zero Vibration Transmission™ system that mechanically decouples the entire loudspeaker from the floor using a combination of metal and elastomer isolation components inside of a multi-part coaxial spike assembly, called "Silent Spikes". The result is an audible improvement in transparency and dynamics.

Retail Price

Il Cremonese ex3me has a suggested manufacturer retail price of 58,000 USD.

Market Availability

Il Cremonese ex3me will be available worldwide from September 2020.



Sonus faber
IL CREMONESE
ex3me

Technical Specification

TYPE	Floorstanding 3.5 ways, 6 speakers
SOUND EMISSION	Direct
ACOUSTICAL LOADING	Bass-Reflex, Floor emission (woofers)/ Rear (midrange) ports. "Stealth Reflex" technology
CABINET	Multilayered wood (sides) and Leather finishing High density wood fiber (cabinet). Massive Avional top and basis
DRIVERS	Tweeter: 30 mm Diamond Like Carbon Beryllium dome diaphragm Midrange: 150mm composite cone, Nd magnet Woofers: 2x180mm composite cone, Fe magnet Infra-woofers: 2x220mm Nanocarbon Fiber/Nomex Honeycomb Long Throw Subwoofer
CROSSOVER FREQUENCY	250 Hz and 2,500 Hz
FREQUENCY RESPONSE	25 Hz – 35,000 Hz
SENSITIVITY (2.83 V @1 m)	92 dBSPL
NOMINAL IMPEDANCE	4 ohm
WIRING OPTIONS	Single/Bi-wiring
SUGGESTED AMPLIFIER POWER OUTPUT	100W – 800W, without clipping
DIMENSIONS (H x W x D)	1,450 x 398 x 622 mm
WEIGHT	84 Kg each

