

MPD config

Output name config

Name	sMS-200-USB
------	-------------

Enter MPD output name

Audio device config

<input checked="" type="radio"/>	XMOS USB Audio 2.0	X20
----------------------------------	--------------------	-----

DSD disable	<input type="radio"/>	DoP	<input checked="" type="radio"/>	Native DSD type 0	<input type="radio"/>	Native DSD type 2	<input type="radio"/>
-------------	-----------------------	-----	----------------------------------	-------------------	-----------------------	-------------------	-----------------------

Select Audio device and option. When you select Native DSD type 2, your DAC supports 32-bit DSD_U32_BE sample formats (e.g. XMOS based USB DACs and Marantz/Kenwood DACs). Type 0 is for using 8-bit DSD_U8 format like the Botic driver for the BeagleBone Black.

MPD buffer config

Audio buffer size	4.0	MB	Buffer before play	0	%
Buffer time	0.2	sec	Period time	5	ms

Enter MPD buffer values

MPD & DLNA feature config

Replay gain	None	OpenHome	<input checked="" type="checkbox"/>	Library auto update	<input checked="" type="checkbox"/>	Mixer type	software
-------------	------	----------	-------------------------------------	---------------------	-------------------------------------	------------	----------

Tidal streaming config

ID or Email		Password		Quality	low
-------------	--	----------	--	---------	-----

Enter your TIDAL ID & Password. And select TIDAL streaming quality according to your account type, 'Low' or 'High' are for Premium account and 'Lossless' is for HiFi account.

Qobuz streaming config

ID or Email		Password		Format	normal
-------------	--	----------	--	--------	--------

Enter your Qobuz ID & Password. And select Qobuz streaming format, 'Normal' is for MP3 and 'Lossless' is for FLAC.